



**CUSTOM FLAME HARDENED, PRECISION COLD FINISH, WEAR RAIL (OPTIONAL GROUND-TO-SIZE)**

**REDI-RAIL®** (formerly Kromite® CD60) is a custom manufactured, precision “wear rail” component. Hardness range from 38/42 or 55/62 Rockwell “C” depending upon the application. It is suited to handle many applications including: transfer rails, conveyor guide rails, machine ways, beef rails, heavy-duty tracks and various OEM parts. Its wear resistant properties far exceed that of “cold roll” steels even after further heat treatment is applied.

**REDI-RAIL®** is engineered to outlast C1045, C1060, 4140, and 6150 in similar applications; is offered with undersized Cold Drawn tolerances.

**REDI-RAIL®**, a complete turn-key approach for precision “wear rail” requirements.

**KEY FEATURES**

**Straightness Furnished** – straightened after thermal treatment to .035” per 10 feet. (restrictions apply).

**Twist and Bow** – custom flattened and de-twisted to your exact requirements upon the application.

**Depth of Case** – as required from up to .125”.

**Hardness of Case** – Material may be hardened from 55/62 Rockwell “C” or tempered down to 38/42 depending upon your application.



**TYPICAL APPLICATIONS**

- Transfer Rails • Machine Ways • Jigs & Fixtures
- OEM Parts • Wear Bars • Conveyor Rails
- Beef Rails • Guides • Heavy-Duty Tracks

**AVAILABLE INVENTORY**

- Flats (1/4” x 1” up to 2” x 6”) • Beef Rail Stock (call for specific details)
- Squares (3/8” up to 4”) • Metric Size Options

*Contact our office for complete details on all custom fabrication components and general machining needs.*

**PHONE: 800.321.9300**  
**EMAIL: INQUIRY@ASSOCIATEDSTEEL.COM**  
**WEB: WWW.ASSOCIATEDSTEEL.COM**